



Born for Low Light

The HIKMICRO ALPEX with advanced sensor technology and image processing to deliver a detailed, full colour image throughout the day automatically adjusting to twilight and continuing to display an amazing full colour image up until total darkness.

ALPEX PRO	MODEL	RANGE	FOV	MAGNIFICATION	CMOS RESOLUTION	RRP
	A50PL KIT	1500m	7.2° × 4.0°	4 - 24	4512 × 2512	\$2,299
	A50PL					\$2,099
ALPEX 4K	A50P	1500m	7.2° × 4.0°	4 - 24	4512 × 2512	\$1,899
	A50EL KIT	1000m	8.8° × 5°	3.5 - 28	3840 × 2160	\$1,999
	A50EL					\$1,799
	A50E					\$1,699
ALPEX 4K LITE	A40EL KIT	800m	10.7° × 6.1°	3.5 - 20.5	3840 × 2160	\$1,699
	A40EL					\$1,499
	A40E KIT					\$1,399
	A40E					\$1,199

Compact yet powerful

High thermal sensitivity, perfect detail recognition. Every detail matters when identifying targets. Less than 20 mK NETD helps identify small details of objects from their background easily and clearly even in the hardest weather and low- light conditions.

PANTHER 2.0

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
PQ50L 2.0	2600m	8.8° × 7°	2.6	640 × 512, 12 μm NETD < 20mK	\$7,999
PQ35L 2.0	2600m	12.5° × 10°	1.82		\$7,299
PH50L 2.0	2600m	5.2° × 3.9°	4.33	384 × 288, 12 μm NETD < 20mK	\$5,899
PH35L 2.0	1800m	7.5° × 5.6°	3.03		\$4,999
** Ballistic Calculator features on all LRF Models					

Powerful & Robust

The HIKMICRO T16 cameras are powerful and robust 4G-equipped cameras ideal for wildlife observation and extremely useful devices for hunting and a variety of other outdoor activities.

TRAIL CAMERA	MODEL	RANGE	FEATURE	RESOLUTION	RRP
	T16	25m Identification Range	0.4 Second Trigger Speed	Video 1080P Image 24MP	\$399
	T16 Twin Pack	2x T16 Trail Cameras			\$759
	SP5000	SOLAR PANEL-Powerbank			\$199



HIKMICRO

See the World in a New Way



STELLAR 3.0

THERMAL TUBE SCOPE



Traditional tube with powerful performance.

The Stellar 3.0 Thermal Scopes feature high-resolution detectors (up to 1280 × 1024), 2560 × 2560 OLED displays, and NETD<15 mK sensitivity. With up to 3100 m detection range, built-in laser rangefinder, ballistic calculation, and 10-hour battery life, they offer precision and reliability for field and forest hunting.

STELLAR 3.0

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP	
SX60LS 3.0	3100m	14.6° × 11.7°	2.5-28.5	1280 × 1024, 12 μm NETD < 15mK	\$11,299	
SQ50L 3.0	2600m	8.8° × 7°	3.6-26.6	640 × 512, 12 μm NETD < 15mK	\$7,499	
SQ35L 3.0	1800m	12.5° × 10°	2.5-24.5		\$6,999	
SH50L 3.0	2600m	5.3° × 4°	6-24	384 × 288, 12 μm NETD < 15mK	\$5,999	
SH35L 3.0	1800m	7.5° × 5.7°	4.2-24.2		\$4,799	
SH35 3.0					\$3,999	

NEOS

THERMAL TUBE SCOPE



Precision Without Pause

HIKMICRO NEOS Thermal Scope is equipped with shutterless technology and the latest Sync Pro algorithm, ensuring excellent targeting accuracy even in challenging moments. With its compact and lightweight design, NEOS also brings great portability especially during long-time hunting.


NEOS	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	NH35L	1800m	7.6° × 5.7°	3.2× - 25.6x	384×288, 12 μm NETD < 18mK	\$3,699
	NH25L	1200m	7.0° × 5.3°	3.5× - 24.5×	320×240, 12 μm NETD < 18mK	\$2,499
	NE25	1200m	7.0° × 5.3°	3.5× - 24.5×	256×192, 12 μm NETD < 18mK	\$1,999

New Zealand Office E-Mail: newzealand@huntsmanoptics.com
New Zealand Office Phone: (03) 789 4112



DEFINE

HOW YOU SEE THE GAME



HABROK

MULTI-SPECTRUM BINOCULARS



*All Habrok range also available in a 940nm option

Enhanced Resolution

The Habrok Pro & 4K models combine thermal and digital optical channels, enhancing outdoor experiences. Compact like traditional binoculars but packed with advanced tech. Detect in thermal, view in optical, and record to built-in memory.

HABROK Pro & 4K	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	HX60LS 4K	3100m / 400m	D 7.3° × 4.1° T 14.6° × 8.8°	D 5.5-22 T 2.6-20	1280 × 1024, 12µm NETD < 18mK	\$11,499
	HQ50L 4K	2600m / 400m	D 7.3° × 4.1° T 8.8° × 5.3°	D 5.5-22 T 3.6-26.6	640 × 512, 12µm NETD < 15mK	\$7,499
	HQ35L 4K	1800m / 400m	D 7.3° × 4.1° T 12.5° × 10.1°	D 5.5-22 T 3-22	640 × 512, 12 µm NETD < 20mK	\$5,799
	HH35L 2.0 4K	1800m / 400m	D 7.3° × 4.1° T 7.5° × 5.6°	D 5.5-22 T 4.0-22	384 × 288, 12µm NETD < 15mK	\$4,499
	HE25L 2.0 4K	1200m / 400m	D 7.3° × 4.1° T 7° × 5.3°	D 5.5-22 T 4.3-17.2	256 × 192, 12µm NETD < 18mK	\$ 3,499

LYNX 3.0 & LYNX S

THERMAL MONOCULAR



*NETD < 15mK

Lightweight & Compact

Compact and light with a very comfortable and robust feel to it, the LYNX Monocular has the ultimate thermal performance housed in a small package. With advanced engineering, the refresh rate is smooth and fast – eliminating the need for recalibration as you scan your hunting zone.

LYNX 3.0 & S	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	LQ35L 3.0	1800m	12.5°×7.5°	1.9 - 15.2	640×512, 12µm, NETD < 15mK	\$4,399
	LQ35 3.0					\$3,899
	LH35 3.0	1800m	7.5° × 4.6°	3.4-27.2	384× 288, 12 µm NETD < 15mK	\$2,899
	LH25 3.0	1200m	10.5° × 6.4°	2.5-20		\$2,499
	LH19 3.0	900m	13.8° × 8.4°	1.9-15.2		\$2,199
	LH15 3.0	750m	11.7° × 8.8°	2.2-17.6	320×240, 12 µm NETD < 18mK	\$1,899
	LE15 3.0	750m	11.7° × 8.8°	2.2-17.6	256 × 192, 12 µm NETD < 20mK	\$1,199
	LE10 3.0	500m	18.0° × 13.6°	1.4-11.2	256 × 192, 12 µm NETD < 20mK	\$999
	LC06 S	250m	24.7° × 18.7°	1.0- 4.0	160 × 120, 17µm*	\$699

FALCON

THERMAL MONOCULAR



Industry Leading Thermal Performance

The Falcon thermal monocular combines an advanced NETD<15 mK sensor with an F0.9 lens, ensuring exceptional imaging even in tough weather. The Falcon boasts a durable design, intuitive controls, and a 5-hour battery. Unique "Image Pro mode" enhances detail, supported by 64GB internal storage.

FALCON	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	FQ50L 2.0	2600m	8.8° × 7°	2.7-21.6	640 × 512, 12 µm NETD < 15mK	\$5,699
	FQ50 2.0					\$4,999
	FQ35 2.0	1800m	12.5° × 10°	1.9-15.2	640 × 512, 12 µm NETD < 20mK	\$4,199
	FQ25	1200m	17.5° × 14°	1.4-11.2		\$3,999
	FH35	1800m	7.5° × 5.7°	3-24	384 × 288, 12 µm NETD < 20mK	\$2,999
	FH25	1200m	10.5° × 7.9°	2.2 – 17.6		\$2,599

CONDOR

THERMAL MONOCULAR



Remarkable image quality

This compact spotter is equipped with a powerful, high-sensitivity NETD<15 mK thermal detector, which captures exceptionally fine detail. The result is a vivid, layered image, which doesn't just make it easy to spot and identify target quarry but also gives a very clear view of the surrounding landscape.

CONDOR	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	CQ50L 2.0	2600m	8.7° × 7°	2.7 - 21.6	640 × 512, 12 µm NETD < 15mK	\$5,299
	CQ35L 2.0	1800m	12.5° × 10°	1.9 - 15.2		\$4,799
	CH35L	1800m	7.5° × 5.6°	3.5 - 28	384 × 288, 12 µm NETD < 20mK	\$3,899
	CH25L	1200m	10.5° × 7.9°	2.5 - 20		\$3,299

THUNDER 2.0

THERMAL SCOPE



Impressive Detail Recognition

With an extremely high thermal sensitivity (NETD<20mK) detector combining a powerful thermal camera of up to 640x512 @12µm @ F1.0, it ensures informative images and an enhanced identification capability even under the slightest temperature differences.

THUNDER 2.0	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	TQ50 2.0	2600m	8.8° × 7°	2.6 - 20.8	640 × 512, 12 µm NETD < 20mK	\$6,799
	TQ35 2.0	1800m	12.5° × 10°	1.8 - 14.6		\$5,599
	TH35P 2.0		7.5° × 5.7°	3 - 24	384 × 288, 12 µm NETD < 20mK	\$4,499
	TH25P 2.0	1200m	10.5° × 7.9°	2.2 - 17.6		\$3,999
	TE25 2.0		7° × 5.3°	3.3 - 26	256 × 192, 12µm NETD < 35mK	\$2,399
	TE19 2.0	1000m	9.2° × 6.9°	2.5 - 19.8		\$1,899

THUNDER ZOOM 2.0

THERMAL SCOPE



Dual FOV Technology

With a 2.2x to 34.6x large magnification realized by the 384 detector @20mK, TH50Z 2.0 is the perfect match for both wooded and open field areas. A F0.8 large aperture also strengthens your viewing ability of objects.

THUNDER ZOOM 2.0	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	TQ60Z 2.0	1800m/ 3000m	12.5° × 10°/ 7.3° × 5.9°	1.8-14.6/ 3.1 - 25	640 × 512, 12 µm NETD < 20mK	\$7,699
	TH50Z 2.0	1200m/ 2600m	10.5° × 7.9°/ 5.3° × 4°	2.2 - 17.4 / 4.3 - 34.6	384 × 288, 12 µm NETD < 20mK	\$5,299

THUNDER 3.0

THERMAL CLIP-ON



*Fixed at base magnification in clip-on mode

Clip-On Versatility

These thermal monoculars boast high-resolution detectors @ 640 × 512, 1920 × 1080 OLED displays, and NETD < 15 mK sensitivity, offering detection ranges up to 2600m. With a 6-hour battery life and 1000 g shock resistance, they deliver top-tier performance in any environment.

THUNDER 3.0	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	TQ50CL 3.0	2600m	8.8° × 7°	×1*	640 × 512, 12 µm NETD < 15mK	\$6,499
	TQ50C 3.0	2600m	8.8° × 7°	×1*		\$5,699
	TQ35CL 3.0	1800m	12.5° × 8°	×1*		\$5,799
	TQ35C 3.0	1800m	12.5° × 8°	×1*		\$5,099
	TH35C 3.0	1800m	7.5° × 5.7°	×1*	384 × 288, 12 µm NETD < 15mK	\$4,499

HIKTac

THERMAL SIGHT



See More, Track Fast

The HIKTac is designed for outdoor field applications, offering sharp thermal detection in low-light and challenging visual conditions. With high thermal sensitivity and a smooth 50Hz refresh rate, it helps users spot and track objects quickly and clearly. The large AMOLED display & optional laser range finder provide an immersive viewing.

HIKTAC	MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
	TC19L	900m	9.2° × 6.9°	1.2 - 9.6	256 × 192, 12 µm NETD < 18mK	\$1,299

A7E

ACTION CAMERA



Your Personal Shooting Coach

The HIKMICRO A7E is designed for hunters, clay shooters and sportsmen who want to capture every shot in sharp 4K detail. Compact and lightweight, it features up to 8x magnification, recoil-activated recording, long battery life and rugged IP67 protection for tough outdoor use.

A7E	MODEL	MAX RECOIL	STORAGE	MAGNIFICATION	VIDEO RESOLUTION	RRP
	A7E	375g/1.7ms	64 GB Built-In	2 - 8	4K @60fps 2.7K @120fps 1080p @ 120fps 720p @120fps	\$899